


At the Cutting Edge of Material Preparation

Ordering Information

Part Number	Description
11-2800	IsoMet High Speed Pro
11-2707	T-Slot Bed Kit
11-2660	Rapid Rail Vise Holder
11-2661	Single Saddle Chuck
11-2662	Double Saddle Chuck
11-2666	1.25" Quick Clamp Vise [30mm]
11-2667	1.5" Quick Clamp Vise [40mm]
11-2655	Dressing Wheel Standard
11-2656	Dressing Wheel 5 And 10 LC
11-2640	Recirculation Tank



Technical Specifications

Operation	Automatic, Manual, or SmartCut control Linear Blade Feed
Motor Power at 220VAC	2.68Hp [2kW]
Main Power	100 - 240VAC, 50-60Hz, 1 Phase
Blade Movement Axis	Horizontal, Linear, Vertical (X, Y, Z)
Blade Position Settings	Horizontal: 0 - 2in [0 - 50mm] Vertical: 0 - 2in [0 - 50mm]
Cut Length Range	.01 - 7.25 in [0.25mm - 184mm]
Feed Rate Range	.04 - 1 in/min [1.2 - 25.4mm/min]
Blade Speed	1000-5000rpm
Cut Capacity Diameter	2.8in [71mm]

Lighting	2 LED Strip Adjustable brightness
Laser	Green Laser
Wafering Blade Diameters	3 - 8in [75 - 200mm]
Abrasive Blade Diameters	5 - 8in [125 - 200mm]
Cut Chamber Size	9in x 20in [228mm x 508mm]
Machine Dimensions	Width: 24in [609.6mm] Depth: 30in [762mm] Height (Hood Opened): 36in [914.4mm] Height (Hood Closed): 19in [482.6mm]
Safety Features	Interlock Hood Switch Emergency Stop
Compliance	CE Directives



BUEHLER Worldwide Headquarters
North America-South America Offices
41 Waukegan Road
Lake Bluff, Illinois 60044-1699 USA
P: 800 BUEHLER (800-283-4537)
P: (847) 295-6500
www.buehler.com | info@buehler.com

European Headquarters
BUEHLER Germany
info.eu@buehler.com

BUEHLER France
info.eu@buehler.com

BUEHLER United Kingdom
info.eu@buehler.com

BUEHLER China
info.cn@buehler.com


BUEHLER Japan
info.japan@buehler.com

BUEHLER Asia-Pacific
info.asia@buehler.com



IsoMet® High Speed Pro

Advanced Precision Cutter



Automatic Dressing System

Maintain consistent cut quality between and during cutting with the automatic dressing system. Reduce the frequency of changing the dressing stick with new optimized dressing wheel design.




Intuitive Controls

Create repeatable and consistent cuts with programmed methods. Simple program setup with action icons.



Rapid Alignment

Minimize setup time by rapid visual alignment with the IsoMet High Speed Pro Laser.



Quick Sample Adjustments

In seconds adjust your sample placement with the rapid rail and tool-less vising system.



Precise Cut Alignment

Align precise cuts quickly by use the 3 axis variable movement of the blade.

Efficient. Consistent. Precise.